

POSEIDON-1750

1750mm dia. Ocean Buoy




POSEIDON-1750
Wreck Marking Buoy

Sealite have a range of mooring chains & accessories - ask your representative today how we can supply your complete mooring solution

The Sealite Advantage

- High visibility red, green, white or yellow as per IALA recommendations
- 3 part product: floatation section, mid section & top section
- Individual colouration of each section to suit IALA colour/configuration recommendations
- Excellent buoyancy & stability
- Easy to deploy & service
- No painting, ever
- Cost effective & environmentally friendly




Optional Day Marks



Environmentally Friendly & Recyclable

Sealite buoy products are made from recyclable materials. As a service to customers, individual components and products at the end of their service life may be returned to Sealite for recycling.



The Sealite POSEIDON-1750 Buoy is manufactured from UV-stabilized, virgin polyethylene and has been specifically designed to withstand the harsh marine environment, and operate reliably with minimal maintenance.

Ports worldwide are realising the advantages of polyethylene buoys over traditional steel models. The colour pigment is added to the polyethylene during the moulding process, which means that the buoy never requires painting.

The polyethylene material also inhibits marine growth, so the buoy requires cleaning less often than steel types.

Significant advantages of the polyethylene buoy allow the interval between servicing to be far greater and users continually report major cost savings.


The POSEIDON-1750 is constructed from 3 parts ensuring ease of deployment and servicing. The float section incorporates two large lifting and mooring points, interconnected by 316-grade stainless steel tie-bars to provide greater strength. The mid-section may be supplied with a large secondary battery enclosure, whilst the top section is designed to carry the buoy's primary payload.



POSEIDON-1750

1750mm dia. Ocean Buoy

The float section is internally cross-braced (■) using stainless steel braces joining each mooring eye to the lifting eye. This ensures mooring and lifting stresses are evenly shared across the structure.



SPECIFICATIONS * POSEIDON-1750

General Characteristics

Available Colours
Focal Plane Height (mm/inches)
Total Float Volume (ltrs/US gallon)
Nominal Freeboard (mm/inches)
Nominal Draft (mm/inches)
Reserve Buoyancy (kgs/lbs)
Maximum Mooring Load (kgs/lbs)
Draft, Maximum (mm/inches)
Freeboard, Minimum (mm/inches)
Safe Working Load, 1pt (kgs/lbs)
Safe Working Load, 2pt (kgs/lbs)
Submergence (kg/cm, lb/inches)
Visual Area (m²/ft²)

Red, Green, White, Yellow as per IALA Recommendations
2500 / 98³/₈ (standard), 3090 / 121⁵/₈ (with spacer)
1650 / 436
445 / 17¹/₂
725 / 28¹/₂
600 / 1323
600 / 1323
970 / 38³/₄
200 / 7⁷/₈
2300 / 5070
3250 / 7165
24.5 / 137
1.75 / 18.8

Physical Characteristics

Material

Rotationally-moulded UV-stabilized virgin polyethylene, internal 316-grade stainless steel bracing, 316-grade stainless steel fittings, slip resistance platform

Wall Thickness (mm/inches)
Ballast (kg/lbs)
Filling
Height (mm/inches)
Width (mm/inches)
Mass (kg/lbs)
Radar Reflector
Product Life Expectancy

16 / ⁵/₈ (float section)
150 / 330 internal concrete
Closed-cell polyurethane foam (float section)
3960 / 156
1750 / 68⁷/₈
436 / 961
Echomax
>20 years

Certifications

Quality Assurance

ISO9001:2008

Intellectual Property

Trademarks

SEALITE® is a registered trademark of Sealite Pty Ltd
5 years

Warranty *

Lantern Options Options Available

Sealite SL-C310, SL-C410, SL-C420, APOLLO-155 or SL-125 series

- Mould-in graphics
- Day marks
- Monitoring Systems (AIS, GSM)

* Specifications subject to change or variation without notice
* Subject to standard terms and conditions

